



## NIPPON POLYESTER PUTTY

### **Product Description:**

*NIPPON POLYESTER PUTTY* is a high solid two-pack putty suitable for filling deep indentations. It is fast drying, easy to sand and is recommended to be used in all automotive refinishing system.

### **Recommended Uses:**

Ideal for filling deep indentations.

### **Properties:**

<b>Colour</b>	: Grey and Brown
<b>Build</b>	: High Build
<b>Pot Life</b>	: 4 to 5 minutes after mixing at 25°C - 30°C.
<b>Mixing Ratio</b>	: 50 parts by weight of Base to 1 part by weight of Hardener.

<b>Application Method</b>	: Apply Nippon Polyester Putty with putty knife. Mix the Base and Hardener thoroughly before applying onto the substrate. The putty should be applied in thin layers until the imperfections are made good. Each layer should be allowed 10 - 15 minutes drying. The final layer of putty can be wet-sanded with #320 grade sandpaper 20 - 30 minutes after application.  Clean and allow putty to dry before applying Nippon Nitrocellulose Putty.
---------------------------	--

### **Surface Preparation:**

Sand surface to be applied with polyester putty with #320 grade sandpaper and remove any rust, dust, grease or oil.

**Safety, Health and Environmental Information:**

Keep container tightly closed and keep out of reach of children or away from food and drink. Ensure good ventilation during application and drying. When applying paint, it is advisable to wear eye protection and aspirator. In case of contact with eye, rinse with plenty of water immediately and seek medical advice. Paint must always be stored in a cool place. When transporting paint, care must be taken. Always keep container in a secure upright position. Dispose of any paint waste in accordance with the appropriate Environmental Quality Regulations.

**Note:**

*The above information is given to the best of our knowledge based on laboratory tests and practical experience. However, since we cannot anticipate or control the many conditions under which our products may be used, we can only guarantee the quality of the product itself.*

*We reserve the right to alter the given data without notice.*

**Standard Packing** : 3.5 kg Polyester Putty Base, 80g Hardener